INDEX

RUBBER CHEMISTRY AND TECHNOLOGY **VOLUME 53, 1980** AUTHOR INDEX*

ABOYTES, P., AND P. MARSH, Hysteresis-effect of carbon black aggregate size (Abstract), (5) 1272

ANGULO-SANCHEZ, J. L., AND P. CABALLERO MATA, Long chain branching in natural hevea rubber, determination by gel permeation chromatography (Abstract), (2) 377 ANZAI, S., see KITAYAMA, M., (1) 1

ARAMBURO, F., see RAMOS, I. L. F., (2) 388

ARCOZZI, A., see PIAZZA, S., (4) 994

BASU, S., see BHOWMICK., A. K., (2) 321; (2) 327
 BAUERLE, J. G., AND J. B. FINLAY, A new processing fluroelastomer having improved fluid resistance (Abstract), (5) 1262

BEADLE, H. C., A non thiourea neoprene accelerator (Abstract), (5) 1268

BHOWMICK, A. K., S. BASU, AND S. K. DE, Scanning electron microscopy of nitrile rubber fractured surfaces, (2) 321 -, AND S. K. DE, Effect of curing temperature and curing system on property-structure

relations of rubber blends, (4) 960

 AND ——, Effect of curing temperature on the technical properties of nitrile rubber and carboxylated nitrile rubber, (1) 107 -, Kinetics of crosslinking and network changes in natural rubber vulcani-

zates with a dithiodimorpholine based accelerator system, (5) 1015

-, G. B. NANDO, S. BASU, AND S. K. DE, Scanning electron microscopy of fractured natural rubber surfaces, (2) \$27 BITTEL, P. A., Processability testing of nitrile elastomers and compounds (Abstract), (2)

989 BOETTCHER, E., D. BRICHZIN, P. DANILOWICZ, AND W. H. KLINGENSMITH, Economic benefits of using processing agents (Abstract), (2) 389

Brazier, D. W., Applications of thermal analytical procedures in the study of elastomers and elastomer systems, (3) 437

-, G. H. NICKEL, AND Z. SZENTGYORGYI, Enthalpic analysis of vulcanization by calorimetry. Thiuram monosulfide/sulfur vulcanization of NR and SBR, (1) 160

BRICHZIN, D., see BOETTCHER, E., (2) 389 BUDZOL, M., see SWOR, R. A., (5) 1215

BYAM, J. G., R. A. SOUFFIE, AND K. D. ZIEGEL, Energy requirements for the processing of elastomers, (5) 1264 BYERS, J. T., see PATEL, A. C., (5) 1272

CADLE, S. H., AND R. L. WILLIAMS, Environmental degradation of tire wear particles, (4)

CASSEL, B., Thermal analysis test methods for characterizing elastomers (Abstract), (5) 1267 CHALIFOUX, J. P., AND É. A. MEINECKE, Force-balance capillary rheometry at low shear rates, (5) 1117

CHEN, C. K., see DOLEZAL, P. T., (5) 1273
CLARK, M. S., Microwave absorption characteristics of carbon black in ethylene-propylene rubber (Abstract), (2) 378

COHEN, R. E., see THIELE, J. L., (2) 313
CORAN, A. Y., AND R. PATEL, Rubber-thermoplastic compositions. Part I. EPDM-polypropylene thermoplastic vulcanizates, (1) 141

Prepared by L. E. Gwin.

- AND -, Rubber-thermoplastic compositions. Part II, NBR-nylon thermoplastic elastomeric compositions, (4) 781
- CYBULA, T. H., Testing of thermoplastic elastomers (Abstract), (2) 382
- CZARNECKI, L., see WHITE, J. L., (4) 823
- DANIELL, A. E., Modern and effective carbon black testing for type identification and quality measurement (Abstract), (2) 382

- DANILOWICZ, P., see BOETTCHER, E., (2) 389
 DE, S. K., see BHOWMICK, A. K., (1) 107; (2) 321; (2) 327; (4) 960; (5) 1015
 DERHAM, C. J., AND A. Y. THOMAS, Natural rubber foundation bearings for earthquake protection-experimental results, (1) 186
- DERRINGER, G. C., The role or statistical experimental design in testing and problem solving (Abstract), (2) 385
- DIEM, H. E., see LATTIMER, R. P., (5) 1170
- DIPINTO, J. G., see SUBRAMANIAN, N. S., (5) 1269
 DOLEZAL, P. T., AND P. S. JOHNSON, Contribution of power profiles to mixing efficiency (2) 252
- -, F. W. HETZEL, AND C. K. CHEN, Mixing optimization on a factory scale
- using mixing profiles, (5) 1273 DONEY, C., see PARIS, W. W., (2) 368
- DREYFUSS, P., L. J. FETTERS, AND D. R. HANSEN, Elastomeric block polymers, (3) 728 DUNN, J. R., see Pristerer, H. A., (2) 357
- EDWARDS, D. C., AND K. SATO, Interaction of silica with functionalized SBR, (1) 66 EDWARDS, K., see LAUTENSCHLAEGER, F. K., (1) 27

- ENTHWHISTLE, J., Product energy and textiles (Abstract), (5) 1265 EVANS, C. W., Energy considerations using particulate polymers (Abstract), (5) 1265
- FATH, M. A., see WALKER, L. A., (2) 386
- FETTERS, L. J., see DREYFUSS, P., (3) 728
- FIELDING-RUSSELL, G. S., AND D. I. LIVINGSTON, Factors affecting cord-to-rubber adhesion by a tire cord adhesion test, (4) 950
- , see KIMBALL, M. E., (4) 936

- FINLAY, J. B., see BAUERLE, J. G., (5) 1262
 FOOTE, L. R., see KILLGOAR, P. C., Jr., (2) 335
 FRISCH, K. C., Recent developments in urethane elastomers and reaction injection molded (RIM) elastomers, (1) 126
- FUNT, J. M., Rubber mixing, (3) 772
- GARDINER, R., Vulcanization energy (Abstract), (5) 1266
- GENT, A. N., AND C. T. R. PULFORD, Wear of metal by rubber, (1) 176 GHATGE, N. D., AND B. M. SHINDE, The synthesis of isocyanate modified novolak resins for use in natural and synthetic rubber, (2) 239
- GLYMPH, E. M., see KAY, E. L., (5) 1273 GONZALEZ, V., Thermal oxidation of elastomers by differential scanning calorimetry (Ab-
- stract), (2) 378
 GOOD, G. W., Decision support for the design of experiments (Abstract), (2) 384
 GRAESSLEY, W. W., AND G. VER STRATE, A simple method for estimating viscosity in highly viscous liquids, (4) 842
- GRIFFIN, W. R., Accelerated testing of noncuring sealants for integral fuel tanks of aircraft (Abstract), (2) 387
- GUTIERREZ, R., see KAY, E. L., (5) 1273
- HANDS, D., The effect of biaxial orientation on the thermal conductivity of vulcanized and unvulcanized rubber, (1) 80
- AND F. HORSFALL, A new method for simulating industrial cure processes (Abstract), (2) 390
- HANSEN, D. R., see DREYFUSS, P., (3) 728 HARRELL, E. R., see NAKAJIMA, N., (1) 14
- HARRIS, H. D., Accounting for product energy (Abstract), (5) 1264
- HERTZ, D. L., JR., Sour hydrocarbons—the elastomer challenge (Abstract), (5) 1269 HETZEL, F. W., see DOLEZAL, P. T., (5) 1273 HIRSCH, A. E., see SUBRAMANIAN, N. S., (5) 1269

- HOOVER, E. R., see LATTIMER, R. P., (2) 346; (5) 1170 HOPPER, R. J., N-sulfonyl-sulfilimines as premature vulcanization inhibitors, (5) 1106

- HORSFALL, F., see HANDS, D., (2) 390
- HYDE, W. E., AND C. E. IVEY, Methods for testing elastomeric compounds for oil and gas wells (Abstract), (5) 1270
- IRAKO, K., see KITAYAMA, M., (1) 1
- ISEDA, Y., see KITAYAMA, M., (1) 1 IVEY, C. E., see HYDE, W. E., (5) 1270
- JAMES, D. I., A broader look at pedestrian friction, (3) 512
- JANZEN, J., AND G. KRAUS, New Methods for estimating dispersibility of carbon blacks in
- rubber, (1) 48

 JENSEN, L. W., see Swor, R. A., (5) 1215

 JOHNSON, P. S., General overview of processability testing (Abstract), (2) 383
- , see DOLEZAL, P. T., (2) 252, (5) 1273
- KAY, E. L., R. GUTIERREZ, E. M. GLYMPH, AND J. J. NIVERT, Guayule shrub deresination (Abstract), (5) 1273
- KENNEDY, K. A., see SHIM-TON, J., (1) 88
 KILLGOAR, P. C., JR., R. A. PETT, R. J. TABAR, AND L. R. FOOTE, An elastomeric energy storage device for automotive engine restart, (2) 335
- KIMBALL, M. E., AND G. S. FIELDING-RUSSELL, Effect of cure temperature on urethane
- networks, (4) 936
 KITAYAMA, M., Y. ISEDA, F. ODAKA, S. ANZAI, AND K. IRAKO, Synthesis and properties of polyoxazolidone elastomers from diepoxides and diisocyanates, (1) 1
- KLINGENSMITH, W. H., see BOETTCHER, E., (2) 389
- KNOWLES, T. M., see PUTMAN, J. B., (2) 387
 KOSHUTE, M. A., AND H. L. STEPHENS, A bromine terminated liquid polybutadiene as a solventless, room temperature adhesive system, (2) 285
- KRAUS, G., see JANZEN, J., (1) 48
- KWON, Y. D., see PREVORSEK, D. C., (5) 1271; (5) 1271
- LAKE, G. J., AND O. H. YEOH, Measurement of rubber cutting resistance in the absence of friction, (1) 210
- LAKE, M., AND G. RAPPAPORT, Determination of free soap in styrene-butadiene latex, (4) 1006
- LATTIMER, R. P., E. R. HOOVER, H. E. DIEM, R. W. LAYER, AND C. K. RHEE, Mech-
- anisms of ozonation of N, N'-di-(1-methylheptyl)-p-phenylendiamine, (5) 1170 -, AND P. M. ZAKRISKI, Characterization of aniline-acetone condensation prod-
- ucts by liquid chromatography and mass spectroscopy, (2) 346 , AND K. R. WELCH, Direct analysis of polymer mixtures by field desorption mass
- spectroscopy, (1) 151 LAUTENSCHLAEGER, F. K., AND K. EDWARDS, Model compound vulcanization-part V. The effect of chemical additives and fillers, (1) 27
- LAWSON, G., AND G. B. WILLOUGHBY, Atmospheric monitoring techniques applicable to the rubber industry (Abstract), (2) 388
- LAYER, R. W., see LATTIMER, R. P., (5) 1170
- LEE, L. J., Polyurethane reaction injection molding: Process, materials, and properties, (3) 542
- LEYDEN, J. J., AND J. M. RABB, Reconstruction of rubber compounds using chemical analysis (Abstract), (2) 383
- LIVINGSTON, D. I., see FIELDING-RUSSELL, G. S., (4) 950
- LLORENTE, M. A., AND J. E. MARK, The effect of chain length distribution on elastomeric properties. III. Non-random networks prepared by using a partially vinyl-selective bis(alkylperoxy)diisopropylbenzene, (4) 988
- LOWMAN, M., The effect of oxygen on compression set (Abstract), (5) 1273 LUCKMAN, E. R., see THROCKMORTON, P. E., (2) 270
- MACARTHUR, A., AND H. L. STEPHENS, Reinforcement as a hindrance in the disentanglement of unknotted chains (Abstract), (2) 379
- MacKenzie, B. T., AND G. T. STRIPPOLI, Use of rubber in petroleum pump cables (Abstract), (5) 1267
- MARK, J. E., see LLORENTE, (4) 988
- _____, see Sharaf, M. A., (4) 982 Marsh, P., see Aboytes, P., (5) 1272
- MARUHASHI, K., see O'NEAL, H., (5) 1263

MATA, P. C., see Angulo-Sanchez, J. L., (2) 377

McCormick, C., Evaluating and utilizing the precision of a test method (Abstract), (2) 384

McGrath, J. E., see Tang, S. H., (5) 1160

Mead, W. T., R. S. Porter, and P. E. Reed, An ESR study of oxidation in uniaxially deformed polybutadiene and polyisoprene, (4) 915

MEAD, W. Y., Molecular fracture in polycholoroprene, (2) 245
MEINECKE, E. A., Comparing the time and rate dependent mechanical properties of elastomers, (5) 1145

—, see Chalifoux, J. P., (5) 1117
—, see Porter, L. S., (5) 1133
—, see Tang, S. H., (5) 1160
—, see Yang, R. M., (5) 1124

MONTE, S. J., AND G. SUGARMAN, The effect of titanate coupling agents on nonblack reinforcing agents, a new vulcanizing agent system for polyepichlorohydrin elasto-mers, azodicarbonamide sponged polyphosphazene homopolymers and property maintenance of lower mooney compounds and other developments (Abstract), (2) 391

MORITA, E., Reactions of resin formers in dry bonding rubber systems, (4) 795

—, S-N compounds as delayed action chemicals in vulcanization, (3) 593, (4) 1013 MORMAN, K. N., see SULLIVAN, J. L., (4) 805 MOTOMOCHI, B., see RAMOS, L. F., (2) 385 MUELLER, W. J., Effect of substituted aromatic gasoline components on properties of a nitrile hose core (Abstract), (5) 1262

NAKAJIMA, N., Elongational flow in mixing elastomers with carbon black, (5) 1088

—, AND E. R. HARREL, Viscoelastic characterization of long branching and gels in

butadiene-acrylonitrile copolymer elastomers, (1) 14 NANDO, G. B., see BHOWMICK, A. K., (2) 327 NICKEL, G. H., see BRAZIER, D. W., (1) 160 NIVERT, J. J., see KAY, E. L., (5) 1273

ODAKA, F., see KITAYAMA, M., (1) 1

Он, H. L., A fatigue-life model of a rubber bushing, (5) 1226

O'NEAL, H., AND K. MURAHASHI, Chemistry and applications of liquid chloroprene polymers containing functional groups, (5) 1263

O'NEAL, H., see WALKER, D. G., (5) 1274

PARIS, W. W., AND C. DONEY, Improved service life of automotive suspension bushings through the use of semi-efficient vulcanization systems, (2) 368

PATEL, A. C., AND J. T. BYERS, The influence of tread grade carbon blacks at optimum loadings on rubber compound properties (Abstract), (5) 1272 PATEL, R., see CORAN, A. Y., (1) 141; (4) 781

PECHHOLD, E., G. PRUCKMAYR, AND I. M. ROBINSON, A new investigation of tetrahydrofuran-based polyether glycols in urethane elastomers, (5) 1032 PETT, R. A., see KILLGOAR, P. C., JR. (2) 335

—, see SULLIVAN, J. L., (4) 805
PFISTERER, H. A., AND J. R. DUNN, New factors affecting the performance of automotive fuel hose, (2) 357
PIAZZA, S., A. ARCOZZI, AND C. VERGA, Modified bitumens containing thermoplastic

polymers, (4) 994

PIGGOTT, M. R., see SHIM-TON, J., (1) 88
PONCE, M. A., AND R. R. RAMIREZ, Mixing process of natural and synthetic polyisoprene rubbers (Abstract), (2) 388

PORTER, L. S., AND E. A. MEINECKE, Influence of compression upon the shear properties of bonded rubber blocks, (5) 1133

PORTER, R. S., see MEAD, W. T., (4) 915

PRENTICE, G. A., AND M. C. WILLIAMS, Numerical evaluation of the state of cure in a

vulcanizing rubber article, (5) 1023

PREVORSEK, D. C., AND Y. D. KWON, Feasability of a low rolling resistance tire suitable for safe high speed driving (Abstract), (5) 1271

-, AND R. K. SHARMA, Effects of cord modulus on rolling deformations in tires (Abstract), (5) 1271

PRUCKMAYR, G., see PECHHOLD, E., (5) 1032

PULFORD, C. T. R., see GENT, A. N., (1) 176
PUTMAN, J. B., C. R. SAMPLES, AND T. M. KNOWLES, Systematic analysis of rubber compounds (Abstract), (2) 387

RABB, J. M., see LEYDEN, J. J. (2) 383 RAMIREZ, R. R., see PONCE, M. A., (2) 388

RAMOS, I. T. F., AND F. ARAMBURO, Rheological characterization of guayule rubber (Ab-

RAMOS, I. I. F., AND F. AKAMBURO, Kneological characterization of guayule rubber (Abstract), (2) 388
RAMOS, L. F., AND B. MOTOMOCHI, Vulcanization of guayule rubber (Abstract), (2) 385
RAPPAPORT, G., see LAKE, M., (4) 1006
REED, P. E., see MEAD, W. T., (4) 915

RHEE, C. K., see LATTIMER, R. P., (5) 1170

RIDHA, R., Characterization of stresses, strains, and deformations of tires, (4) 849

RIFFLE, J. S., see TANG, S. H., (5) 1160

ROBINSON, I. M., see PECHHOLD, E., (5) 1032

SAMPLES, C. R., see PUTMAN, J. B., (2) 387
SATO, H., AND Y. TANAKA, H. NMR study of polyisoprenes, (2) 305

see EDWARDS, D. C., (1) 66

SCHLADEMAN, J. A., Hydrocarbon resins and their effect on the sulfur vulcanization of SBR (Abstract), (2) 386

SCHURING, D. J., The rolling loss of pneumatic tires, (3) 600 SCHWARZ, H. F., Carboxylated nitrile/PVC fluxed blends for premium quality products (Abstract), (5)

Carboxylated nitrile rubbers contribute oil resistance to chlorosulfonated polyethylene membranes (Abstract), (5) 1261

SHARAF, M. A., AND J. E. MARK, The effects of crosslinking and strain on the glass transition temperature of a polymer network, (4) 982

SHARMA, R. K., see PREVORSEK, D. C., (5) 1271

SHELL, R. L., Test for evaluating extrusion resistance for oil well packer applications, (5) 1239

SHIM-TON, J., K. A. KENNEDY, M. R. PIGGOTT, AND R. T. WOODHAMS, Low temperature dynamic properties of bitumen-rubber mixtures, (1) 88

SHINDE, B. M., see GHATGE, N. D., (2) 239 SNOWDEN, J. C., Vibration isolation: use and characterization, (5) 1041

SOUFFIE, R. A., see BYAM, J. G., (5) 1264

SPARKS, D. L., The carbon black feedstock outlook 1979-1984 (Abstract), (2) 381

STAN, A. V., Thermovision 680 thermographic display as a tire testing tool (Abstract), (2) 381

STEPHENS, H. L., see KOSHUTE, M. A., (2) 285

STEPHENS, H. L., see MACARTHUR, A., (2) 379
STEPHENS, H. L., see M choloroprene synthetic elastomer (Abstract), (5) 1269

SUGARMAN, G., see MONTE, S. J., (2) 391

SULLIVAN, J. L., K. N. MORMAN, AND R. A. PETT, Non-linear viscoelastic characterization of a natural rubber gum vulcanizate, (4) 805

SVANSON, S. E., see SVENSSON, L. G., (4) 975

SVENSSON, L. G., AND S. E. SVANSON, An NMR investigation of the interaction between carbon black and cis-polyisoprene, (4) 975

SWOR, R. A., L. W. JENSON, AND M. BUDZOL, Ultrafine recycled rubber, (5) 1215 SZENTGYORGYI, Z., see BRAZIER, D. W., (1) 160

TABAR, R. J., see KILLGOAR, P. C., JR., (2) 335

TANAKA, H., see WHITE, J. L., (4) 823 TANAKA, Y., see SATO, H., (2) 305

TANG, S. H., E. A. MEINECKE, J. S. RIFFLE, AND J. E. MCGRATH, Structureproperty studies on a series of polycarbonate-polydimethylsiloxane block copolymers, (5) 1160

THIELE, J. L., AND R. E. COHEN, Thermal expansion phenomena in filled and unfilled natural rubber vulcanizates, (2) 313

THOMAS, A. Y., see DERHAM, C. J., (1) 186
THROCKMORTON, P. E., AND E. R. LUCKMAN, Halogen-containing aminimide compounds as tire cord-adhesives, (2) 270

TOBISCH, K., Contribution to the mathematical description of stress-strain behavior of elastomers, (4) 836

VERGA, C., see PIAZZA, S., (4) 994 VER STRATE, G., see GRAESSLEY, W. W., (4) 842 VETTOR, F. W., Future outlook for energy costs and availability (Abstract), (5) 1266

WALKER, D. G., AND H. O'NEAL, Modern techniques for communication of scientific/

technical information (Abstract), (5) 1274
WALKER, L. A., AND M. A. FATH, Improved dynamic properties in tires—reduced rolling resistance (Abstract), (2) 386

WELCH, K. R., see LATTIMER, R. P., (1) 151
WERSTLER, D. D., Analysis of cured, filled elastomeric compounds by ¹³C NMR, (5) 1191
WHITE, J. L., L. CZARNECKI, AND H. TANAKA, Experimental studies of the influence of particle and fiber reinforcement of the rheological properties of polymer melts, (4) 823

WILLIAMS, M. C., see PRENTICE, G. A., (5) 1023 WILLIAMS, R. L., see CADLE, S. H., (4) 903 WILLOUGHBY, B. G., see LAWSON, G., (2) 388

WOOD, L. A., Molecular interpretations of modulus and swelling relations in natural rubber crosslinked by dicumyl peroxide, (1) 116 WOODHAMS, R. T., see SHIM-TON, J., (1) 88

YANG, R. M., AND E. A. MEINECKE, Dynamic properties of SBS block copolymers, (5) 1124 YANO, S., Changes in the dynamic modulus during thermal degradation of polyisoprene vulcanizate, (4) 944 YEOH, O. H., see LAKE, G. J., (1) 210

ZAKRISKI, P. M., see LATTIMER, R. P., (2) 346

ZHENG-REN, Z., A new concept of tire load inflation formulae, (2) 229 ZIEGEL, K. D., see BYAM, J. G., (5) 1264

SUBJECT INDEX*

Abrasion, effect on NBR fracture, (2) 321 effect on NR fracture, (2) 327 of metals by rubber, (1) 176

of metals by rubber, (1) 176 Abstracts of papers; Fall 1979, (2) 377; Spring 1980, (5) 1261

Accelerators, delayed action (review), (3)

effects on elastomer blend properties, (4) 960

non-thiourea, for CR, (5) 1268

Acetone, aniline condensate, characterization of, (2) 346

Activation energy, of oxidation, calculation of, (2) 378

Adhesion, dry bonding systems for, (4) 795 tire cord, test for, (4) 950

Adhesion promoters, titanates as, (2) 391 Adhesives, liquid functionalized CR for, (5) 1268

brominated polybutadiene, (2) 285 tire cord, aminimides, (2) 270

Aminimides, as tire cord adhesives, (2) 270 3-Aminophenol, reactions in dry bonding systems, (4) 795 Aminothiocarbamyl, rubber accelerator (re-

view), (3) 393 Aniline, acetone condensate, characteriza-

tion of, (2) 346
Anionic polymerization, of block polymers

(review), (3) 728 Antioxidants, evaluation by DSC (review),

(3) 437 identification by field desorption mass spectroscopy, (1) 151

Antiozonants, ozonation product analysis of, (5) 1170 service life effect on NR suspension bush-

ings, (2) 368 Antivibration mountings, elastomer usage as, (5) 1041

Aramid, fiber effects on polystyrene rheology, (4) 823
Asphalt, low temperature properties of

rubber mixtures, (1) 88
Atmospheric monitoring, of rubber proc-

essing plants, (2) 388 Authors, Guide for, (3) G58

Automotive applications, elastomeric restarter for, (2) 335

fatigue life model for suspension bushings, (5) 1226 Bearings, foundation, NR, (1) 186 Benzene, substituted, NBR resistance to, (5) 1262

Benzoquinone, effect on model compound vulcanization, (1) 27

Bis(alkylperoxy)diisopropylbenzene, molecular weight distribution effect on elastomers cured with, (4) 988

Bisphenol A, butylated, identification by field desorption mass spectroscopy, (1) 151

diglycidyl ether, polyoxazolidone synthesis, (1) 1

Bitumen, low temperature properties of elastomer mixtures, (1) 88 thermoplastic elastomer blends, (4) 994

Blends, elastomeric, cure temperature and system effects, (4) 960

Block polymers, bitumen blends, (4) 994 elastomeric (review), (3) 728 structure-property relations, (5) 1160 styrene-butadiene, dynamic properties, (5)

1124 sytrene-butadiene, rheology of, (5) 1117 Bloom, identification by field desorption

mass spectroscopy, (1) 151 Bonding systems, resin former reactions in, (4) 795

Book Reviews
Adhesive Technology Developments
since 1977, (2) G40

Antioxidants—Recent Developments, (2) G39

Chemorheology of Polymers, (3) G66 Developments in Polymer Degradation— 2, (3) G66

Developments in Polymer Fracture-1, (4) G94

Developments in Polymer Stabilization— 1, (2) G39

Developments in Rubber Technology—I. Improving Product Performance, (4) G94

Macromolecular Syntheses, (5) G103 Physical Chemistry of Filled Polymers, (1) G28

The Chemistry of Silica: Solubility, Polymerization, Colloid, and Surface Properties and Biochemistry, (1) G27

Branching, long chain, in NR, (2) 377 of NBR, viscoelasticity effect, (1) 14

^{*}Prepared by L. E. Gwin.

Branching density, of NR, (2) 377

Bromobutyl rubber, mixing optimization of, (5) 1273

Bushing, fatigue-life model of, (5) 1226 suspension, service life of, (2) 368

Butadiene, block copolymer with styrene, dynamic properties of, (5) 1124 rheology of, (5) 1117

Butadiene rubber (BR), ¹³C NMR analysis of, (5) 1191

Butyl rubber (IIR), ¹³C NMR analysis of (5) 1191

metal wear by, (1) 176 mixing efficiency, calculation of, (2) 252

Cable, petroleum pump, elastomer usage in, (5) 1267

Calcium, fatty acid salts, as processing agents, (2) 389

Calcium carbonate, rheological effects on polystyrene melts, (4) 823

polystyrene melts, (4) 823 Calcium hydroxide, viscosity effect on rubber-bitumen mixtures. (1) 88

Calcium sulfate, rheological effects on polystyrene melt, (4) 823

Capillary rheometer, force-balance, low shear rate usage, (5) 1117

use in carbon black evaluation, (5) 1272 Carbon-13, NMR spectra of elastomer vulcanizates, (5) 1191

Carbon black, dispersibility estimation in rubber, (1) 48

effect on compound properties at optimum loading, (5) 1272

effect on GR, IR, NR mixing, (2) 388 effect on GR rheology, (2) 388

effect on model compound vulcanization, (1) 27

effect on NR crosslinking kinetics, (5) 1015

elongational flow effect during mixing, (5) 1088

feedstock outlook for, (2) 381 hysteresis effect in tire treads, (5) 1272

identification by thermal analytical techniques (review), (3) 487 interaction with IR, (4) 975

microwave absorption in EPDM, (2) 378 NR thermal expansion effect, (2) 313 rheological effects on polystyrene melts, (4) 823

testing methods for, (2) 382

Card-phenol, phenolic resin processing aids from, (2) 239

Cashew nut shell liquid (CNSL), phenolic resin processing aids from, (2) 239

Cellulose fiber, polystyrene rheology effect of, (4) 823

Chain entanglement, model for, (2) 379 Chain extenders, for polyurethane elasto-

mers, (1) 126 Chemical resistance, of elastomeric fuel tank sealants, (2) 387

Chemorheology, of IR vulcanizates, (4) 944

Chlorosulfonated polyethylene (CSM), oil resistance of NBR blends, (5) 1261

Chromatography, gas, product analysis of antiozonant ozonation, (5) 1170

gas-liquid, of model compound vulcanizates, (1) 27

liquid, aniline-acetone condensates, (2)
346
liquid, product analysis of antiozonant

liquid, product analysis of antiozonant ozonation, (5) 1170

Coefficient of variation, test variability estimation, (2) 384

Communication, scientific, techniques for, (5) 1274

Complex moduli, of NR gum vulcanizate,
(4) 805

Compound analysis, of vulcanizates, (2) 383 Compression modulus, of elastomers in shear, (5) 1133

Compression set, oxygen effect on, (5) 1273 Computer applications, decision support for experimental design, (2) 384 statistical experimental design in testing,

(2) 385

tire stress analysis, (4) 849 Conductivity, thermal, biaxial orientation effect on, (1) 80

Continuous mixers, for elastomers (review), (3) 772

Continuous vulcan zation, energy requirements for, (5) 1266

Copolyether glycols, ethylene oxide-tetrahydrofuran, for urethane elastomers, (5) 1032

Cord, tire, test for rubber adhesion, (4) 950 Coupling agents, adhesion promoters in BR adhesives, (2) 285 itanates as, (2) 391

Creep, elastomer viscoelastic property determination, (5) 1145

Critical micelle concentration (CMC), in SBR latices, (4) 1006

Crosslink density, curing temperature effect on NBR blends, (1) 107

of BR solventless adhesives, (2) 285 of EPDM-polypropylene thermoplastic elastomers, (1) 141 of NR vulcanizates, (5) 1032

Crosslinking, effect on polymer glass transition, (4) 982 of peroxide-cured NR, modulus-swelling

relations, (1) 116 Crosslinking kinetics, of NR, (5) 1032

Crystallinity, of elastomers, analysis of, (review), (3) 437

Crystallization, stress-induced, of polyoxazolidone elastomers, (1) 1

Cure, state of, calculation method for, (5) 1023

Cure temperature, effect on NBR properties, (1) 107 effect on rubber blend properties, (4) 960 effect on urethane polymer properties, (4)

936

Curing, microwave, of black-filled EPDM, (2) 378

simulation of, (2) 390

mechanism of, polyurethane RIM applications (review), (3) 542

Cutting, rubber, mechanism of, (1) 210 Cutting resistance, of rubber, (1) 210

Cyclohexylthioamines, as prevulcanization inhibitors (review), (3) 393

Decision support, use for experimental design. (2) 384

Degradation, environmental, of tire wear

particles, (4) 903

Deresination, of GR via extraction, (5) 1273 Derivative thermogravimetric analysis (DTG), elastomer analysis by (review), (3) 437

Dialysis, free soap determination in SBR latex, (4) 1006

Diamines, temperature effect on polyurethane cure with, (4) 936

Dicumyl peroxide, modulus-swelling relations in NR cured with, (1) 116

Die swell, of elastomers during mixing, (2) 383

of NBR, (2) 389

poxides, polyoxazolidone from, (1) 1 Diepoxides, synthesis

Differential scanning calorimetry (DSC), antioxidant efficiency determination in elastomers, (2) 378

elastomer applications (review), (3) 437 elastomer characterization via, (5) 1267 of thiuram monosulfide/sulfur vulcani-

zates, (1) 160

Differential thermal analysis (DTA), elastomer applications (review), (3) 437 Diisocyanates, polyoxazolidone synthesis from, (1) 1

Dimethylammonium hydrogen isophthalate, accelerator for CR, (5) 1268

Diphenylmethane-p, p'-diisocyanate, identification by field desorption mass spectroscopy, (1) 151

Dispersion, during rubber mixing (review), (3)772

of carbon black in elastomers, (1) 48; (5)

Dithioamines, as rubber accelerators (review), (3) 393

Dithiodimorpholine, crosslinking kinetics of NR cures accelerated by, (5) 1015

Dynamic mechanical spectroscopy, of polycarbonate-polydimethylsiloxane block polymers, (5) 1160

Dynamic modulus, of IR during thermal degradation, (4) 944

of NR gum vulcanizate, (4) 805 Dynamic properties, of bitumen-rubber mixtures, (1) 88 of CR engine mounts, (5) 1269

of elastomers, rolling resistance effect (review), (3) 600

of rubber in antivibration mountings, (5) 1041

of SBS block copolymers, (5) 1124 of tires, improvements of. (2) 386

Dynamic vulcanization, of EPDM-polypropylene

thermoplastic elastomers, (1) 141

Dynamometer, rolling resistance in tires (review), (3) 600; (2) 386

Earthquake protection, NR foundation bearings for, (1) 186

Ecology, tire wear particle effect on, (4) 903 Efficient vulcanization (EV), accelerators for (review), (3) 393

Electrical applications, of thermoplastic elastomers, (2) 382

Electron spin resonance (ESR), CR analysis, (2) 245 oxidation of BR and IR, (4) 915

Elongational flow, during elastomer mixing, (5) 1088

Energy, conservation of, (5) 1264 cost outlook and availability, (5) 1266 particulate rubber requirements, (5) 1265 requirements for continuous vulcanization, (5) 1266

requirements for elastomer processing, (5) 1264

textile manufacture requirements, (5)

Energy storage device, for automobile restart, (2) 335 Enthalpy, of thiuram monosulfide/sulfur

vulcanization, (1) 160 Environment, monitoring of, in rubber factories, (2) 388

tire wear particle effect on, (4) 903 Epichlorohydrin elastomers, titanate coup-

ling agents for, (2) 391 Ethanol, fuel hose resistance to, (2) 357 Ethylene oxide, tetrahydrofuran copolyether

in urethane elastomers, (5) 1032 Ethylene-propylene-diene polymers (EPDM), ¹³C NMR analysis of, (5) 1191 metal wear by. (1) 176

microwave absorption characteristics of, (2)378

petroleum pump cable usage, (5) 1267 polypropylene blends, (1) 141

Experimental design, decision support for, (2) 384 testing and problem solving usage of, (2)

385 Extraction, of GR resin, stress-strain effect,

(2) 385 optimization during GR deresination, (5) 1273

Extrusion, energy requirements for, (5)

of elastomers, review of, (2) 383 Extrusion resistance, of oil well seals, (5) 1239

Failure mechanism, of NBR vulcanizates, (2) 321

Fatigue model, for rubber suspension bushing, (5) 1226

Fatigue resistance, of CR engine mounts, (5) 1269

Fatty acids, rubber processing aids, (2) 389 Feedstock, carbon black, outlook for, (2) 381

Field desorption mass spectroscopy, anilineacetone condensate characterization by, (2) 346

polymer chemical analysis by, (1) 151 Filler, chain disentanglement effect, model

for, (2) 379 Flow, elongational, during rubber mixing, (5) 1088

gravity-driven, of viscous liquids, (4) 842 Fluid resistance, of fluoroelastomers, (5)

Fluoroelastomers, fluid resistance of, (5) 1262

fuel tank sealants, (2) 387

sour hydrocarbon resistance, (5) 1269 Force-balance rheometer, SBS block copolymer rheology at low shear, (5) 1117

Fracture, molecular, of CR, (2) 245 of NBR surfaces, (2) 321 of NR, (2) 327

Friction, effect on rubber cutting resistance, (1) 210

pedestrian (review), (3) 512 rolling, in tires (review), (3) 600

Fuel consumption, tire rolling resistance effect on (review), (3) 600

Fuel hose, performance of, (2) 357 Fuel tanks, aircraft, testing of, (2) 387

Gas chromatography, pyrolysis, use in rubber compound reconstruction, (2) 383

Gasohol, fluoroelastomer resistance to, (5) 1262

NBR fuel hose resistance to, (2) 357 Gasoline, automotive fuel hose resistance to, (2) 357

fluoroelastomer resistance to, (5) 1262 NBR hose core resistance to, (5) 1262

Gel, effect on NBR viscoelasticity, (1) 14 Gel permeation chromatography (GPC), determination of NR long chain

branching by, (2) 377 Glass beads, rheological effect on polystyrene melts, (4) 823

Glass fiber, rheological effect on polystyrene melts, (4) 823

Glass transition temperature (T_g) , crosslinking and strain effects, (4) 982 determination by DSC and DTA (review),

(3) 437 determination by thermal analysis, (5) 1267

Guayule rubber (GR), antioxidant efficiency in, (2) 378 curing properties versus NR, (2) 385 deresination of, (5) 1273

mixing properties versus IR and NR, (2)

rheology of, (2) 388 Guide for Authors, (3) G58

Halogen, determination in rubber compounds, (2) 383

Heat buildup, effect on NBR fracture, (2) 321

of EPDM during microwave exposure, (2) 378

Heat resistance, of polyoxazolidone elastomers, (1) 1

Heels, shoe, slippage factors (review), (3) 512

Hexamethylenetetramine, reactions in dry bonding systems, (4) 795

Hexamethylphosphorictriamide, catalyst for polyoxazolidone elastomer synthesis, (1) 1

Homogenizing agents, economic benefits of, (2) 389

Hose, fuel, performance of, (2) 357 fuel, resistance to aromatic components, (5) 1262

use of carboxylated NBR/PVC blends as, (5) 1261

Hydrocarbon resins, effect on SBR vulcanization, (2) 386 Hydrolytic stability, of brominated BR ad-

hesives, (2) 285 Hydroquinone, model compound vulcani-

zation effect, (1) 27 Hydroxyl groups, in functionalized SBR, silica effect on reinforcement of, (1) 66 Hysteresis, carbon black effect in tire treads,

(5) 1272 effect on tire rolling deformation, (5) 1271

(Iminodithio)dithiazoles, as rubber accelerators (review), (3) 393

Inflation load, calculation method for, (2) 229

Inflation growth, in tires, (4) 849

Information, scientific, modern techniques for communication, (5) 1274

Infrared spectroscopy, attenuated total reflectance, of ozonation products, (5) 1170 of polyoxazolidones, (1) 1

of rubber, in compound reconstruction,

(2) 383 Injection molding, energy requirements for, (5) 1264

of elastomers, (2) 383 Insulation, electrical, thermoplastic elastomers as, (2) 382

Internal mixers, for elastomers (review), (3)

Isocyanates, for urethane elastomers, (1) 126 novolak resin modifiers for rubber applications, (2) 239 Isocyanurates, modified urethane elastomers, (1) 126

K factor, use for tire load inflation calculations, (2) 229

Lignin, effect on NBR fracture, (2) 327 Liners, reservoir, oil resistance improvements. (5) 1261

Liquid chromatography, aniline-acetone condensate characterization by, (2) 346

Magnesium chloride, catalyst of polyoxazolidone elastomer synthesis, (1) 1

Mass spectroscopy, aniline-acetone condensate characterization, (2) 346 field desorption, ozonation product anal-

ysis, (5) 1170 field desorption, rubber chemical analy-

sis, (1) 151

Mechanical loss, relation to tire rolling re-

sistance, (5) 1271 Mechanical properties, of elastomers, (5)

1145 Membranes, water, oil resistance of, (5)

1261 Mercaptan, model compound vulcanization

effect, (1) 27 Mercaptobenzothiazole (MBT), use with prevulcanization inhibitors, (5) 1106

Metal oxide, effect on model compound vulcanization, (1) 27

Methanol, fuel hose resistance to, (2) 357 Mica, rheological effects on polystyrene melts, (4) 823

Microstructure, of IR, using NMR spectroscopy, (2) 305

Microwave absorption, by carbon blackloaded EPDM, (2) 378 Mill mixing, of elastomers (review), (3) 772 Mixing, comparison of GR, NR, and IR,

(2) 388 efficiency of, (2) 252 energy requirements for, (5) 1264 optimization of, (5) 1273

of elastomers (review), (2) 383; (3) 772 Model compound vulcanization, filler and additive effects, (1) 27

Modulus, of peroxide-cured NR, swelling relation, (1) 116

Mold design, for RIM applications (review), (3) 542 Monitoring, atmospheric, in rubber factories, (2) 388

Mooney-Rivlin constants, of peroxide-cured NR, (1) 116

NR, (1) 116 2-Morpholinodithiobenzothiazole, rubber ac-

celerator (review), (3) 393 Morphology, of polycarbonate-polydimethylsiloxane block polymers, (5)

Motor mounts, dynamic properties of, (5) 1269

N-(aminothio)imide, cure modifier (review), (3) 393 Natural rubber (NR), antioxidant efficiency

in, (2) 378 analysis by thermal techniques (review), (3) 437

automotive restarter, (2) 335 biaxial orientation effect on conductivity,

(1) 80

13C NMR analysis of, (5) 1191

crosslinking kinetics of dithiodimorpholine-accelerated cure, (5) 1015 cure simulation of, (2) 390 cutting resistance of, (1) 210 enthalpic analysis of, (1) 160 foundation bearings of, (1) 186 fracture of, (2) 327

long chain branching in, (2) 377 metal wear by, (1) 176 mixing properties versus GR and IR, (2)

388 modulus-swelling relations, after perox-

ide cure, (1) 116 non-linear viscoelasticity of, (4) 805 oxygen effect on compression set, (5) 1273

processing aids for, (2) 239 service life of suspension bushings, (2) 368

stress-strain properties versus GR, (2) 385 thermal expansion of, (2) 313 use in antivibration mountings, (5) 1041 use of recycled rubber in, (5) 1215

NBR, see nitrile rubber Netting theory, of tire mechanics, (4) 849 Networks, non-random, chain length dis-

tribution effects on, (4) 988 Nitrile rubber (NBR), blends with nylon, (4) 781 carboxylated, bitumen mixtures, (1) 88

carboxylated, blends with NBR, (1) 107 carboxylated, blends with PVC, (5) 1262 carboxylated, oil resistance of CSM blends, (5) 1261

chain branching in, (1) 14 CR blends, as engine mounts, (5) 1269 curing temperature effect, (1) 107 effect of gasoline aromatics on, (5) 1262 energy requirements in powdered rubber, (5) 1265

fracture surfaces of, (2) 321 gasohol resistance of, (2) 357 processability of, (2) 389

use in petroleum pump cable, (5) 1267 Nitrogen, compression set effect in NR and

SBR, (5) 1273 N, N'-di(1-methylheptyl)-p-phenylenediamine, ozonation mechanism of, (5) 1170

N, N'-dithiodimorpholine, rubber accelerator (review), (3) 393

Nuclear magnetic resonance spectroscopy (NMR), ¹³C, cured elastomer analysis by, (5) 1191

carbon black-IR interactions, (4) 975 of IR, (2) 305

Nylon, modulus effect on rolling resistance, (5) 1271 NBR blends, (4) 781

Oil resistance, of carboxylated NBR/PVC blends, (5) 1262 of CSM-NBR blends, (5) 1261

of NBR-nylon blends, (4) 781 of petroleum pump cable insulation. (5)

of urethane elastomers, (5) 1032

Oil wells, elastomers as packer rings and seals, (5) 1270

extrusion resistance of elastomer seals for, (5) 1239

Optical density, of carbon black dispersions, (1) 48

Orientation, biaxial, effect on rubber conductivity, (1) 80

Oxidation, of BR and IR during processing, (4) 915 thermal, determination by DSC, (2) 378

Oxygen, effect on NR and SBR compression set, (5) 1273

effect on metal abrasion by elastomers, (1) 176

Ozonation, of N, N'-di-(1-methylheptyl)p-phenylenediamine, (5) 1170

Packer rings, extrusion resistance of, (5)

performance testing of, (5) 1270 Particle size, of carbon black, (2) 382

Particulate rubber, energy requirements of, (5) 1265

Paving material, low temperature dynamic properties of rubber mixtures, (1) 88 Pedestrian friction (review), (3) 512

3-Pentadecylphenol, isocyanate-modified phenolic resin from, (2) 239 Pentaethylenehexamine, BR curative, (2)

Permeability, of fuel hose to gasohol, (2)

Phenolic resins, isocyanate-modified, for rubber applications, (2) 239

Peroxides, chain length distribution effect of, (4) 988

model compound vulcanization effect, (1)

Phenylenediamine, antiozonant for NR suspension bushings, (2) 368

reactions in dry bonding systems, (4) 795 Phosphazenes, fluorinated, fuel tank sealants, (2) 387

Phosphinothioylaminosulfides, rubber accelerators (review), (3) 393

Plasticizers, identification by thermal analytical techniques (review), (3) 437 liquid functionalized CR as, (5) 1263

Pollution, air, in rubber factories, (2) 388 Polyamines, as functionalized liquid CR curatives, (5) 1263

Polybutadiene (BR), analysis by thermoanalytical methods (review), (3) 437

antioxidant efficiency in, (2) 378 brominated, solventless adhesives, (2) 285 cutting resistance of, (1) 210

enthalpic vulcanization analysis by calorimetry, (1) 160

liquid, bitumen mixtures, (1) 88 metal wear by, (1) 176

oxidation during processing, (4) 915 Polycarbonate, block copolymer with poly-dimethylsiloxane, (5) 1160

Polychloroprene (CR), dynamic properties of, (5) 1269

liquid, functional group-containing, (5) 1263

metal adhesives for, (2) 285 molecular fracture in, (2) 245

non-thiourea accelerator for, (5) 1268 Polydimethylsiloxane, block copolymer

with polycarbonates, (5) 1160 Polyester, tire cord, modulus effect on tire

rolling deformation, (5) 1271 tire cord, aminimide adhesives, (2) 270

Polyether, cure temperature effect on polyurethanes from, (4) 936 from tetrahydrofuran and ethylene oxide,

(5) 1032Polyethylene, EPDM blends as thermoplastic elastomers, (1) 141

titanate coupling agents for, (2) 391 Polyethylenimine, BR adhesive curative, (2)

Poly(isobutyl methacrylate), crosslinking and strain effects on T_g of, (4) 982

Polyisocyanate, curative for functionalized liquid CR, (5) 1263 Polyisoprene (IR), analysis by thermoana-

lytical methods (review), (3) 437 ¹³C NMR analysis of, (5) 1191

carbon black interactions, (4) 975 dynamic modulus of, during thermal degradation, (4) 944

mixing properties versus GR and NR, (2) 388 NMR spectra of, (2) 305

oxidation of, during processing, (4) 915 Polyolefins, EPDM blends, as thermoplastic elastomers, (1) 141

Polyoxazolidones, synthesis from diepoxides and diisocyanates, (1) 1

Polyoxytetramethylene glycol, polyoxazolidones from, (1) 1 Polypentenamer, metal wear by, (1) 176

Polyphosphazenes, titanates as coupling agents for, (2) 391 Polypropylene, EPDM blends, (1) 141

rheology of bitumen blends, (4) 994 Polystyrene, rheological properties of filled

melts, (4) 823 Polyurethanes, block polymers (review), (3)

cure temperature effect, (4) 936 extract identification by field desorption

mass spectroscopy, (1) 151 reaction injection molding of (review), (3) 542

tetrahydrofuran polyether glycol-based. (5) 1032

Poly(vinyl acetate), crosslinking and strain

effects on T_s, (4) 982 Poly(vinyl chloride) (PVC), NBR blends, (5) 1262

NBR blends, fuel resistance of, (2) 357 Power curves, calculation of IIR mixing efficiency, (2) 252

Power integrator, rolling resistance measurement by, (2) 386

Power profiles, mixing efficiency calcula-tions using, (2) 252

mixing optimization, (5) 1273 Precision, test methods, evaluation of, (2) 384

Prevulcanization inhibitors, in dry bonding systems, (4) 795

N-sulfonyl-sulfilimines as, (5) 1106 (review), (3) 393

Process oils, identification by thermoanalysis (review), (3) 437

Processability, of NBR, (2) 389 of NBR, branching effect, (1) 14

Processing, of elastomers, review of, (2) 383 Processing aids, economic benefits of, (2) 389

isocyanate-modified novolaks, (2) 239 titanates as, (2) 391

Product energy, accounting methods for, (5) 1264

Quality assurance, test method precision for, (2) 384

Reaction injection molding (RIM), of polyurethanes (review), (3) 542 of urethane elastomers, (1) 126

Reclaim, tire, bitumen mixtures, (1) 88 Recycled rubber, usage in rubber com-pounding, (5) 1215

Reinforcement, of elastomers, disentanglement hindrance effect, (2) 379 of functionalized SBR by silica (1) 66

Reinforcement factor, for carbon black in rubber, (5) 1272

Resorcinol, reactions in dry bonding systems, (4) 795

Rheology, of bitumen-thermoplastic elastomer blends, (4) 994 of elastomers, time-rate effects, (5) 1145

of filled polystyrene melts, (4) 823 of GR, (2) 388 of viscous liquids, (4) 842

Rheometer, capillary, at low shear rates, (5)

Rolling deformation, tire cord modulus ef-

fect on, (5) 1271 Rolling resistance, of tires (review), (3) 600 reduction in passenger tires, (2) 386; (5) 1271

Rubber Division, ACS, bylaws (1) G13 Best Paper Awards (2) G35, (4) G84 Charles Goodyear Medalist (3) G68 Guide for Authors (3) G58

library and information service (1) G11; (2) G36; (3) G55; (4) G91; (5) G100 officers and committees, (1) G1; (2) G33;

(3) G53; (4) G81; (5) G97 policy on technical papers (1) G26; (2) G38; (3) G57; (4) G93; (5) G102 program for Fall meeting 1980, (4) G85 program for Spring meeting 1980, (1) G4

Scanning electron microscopy, of NBR fracture surfaces, (2) 321

of NR fracture surfaces, (2) 327 Sealants, elastomeric, for aircraft fuel tanks, (2) 387

Seals, oil well, extrusion resistance of, (5) 1239

oil well, performance testing of, (5) 1270 Semi-efficient vulcanization, of automotive suspension bushings, (2) 368

Shear-compression properties, of elastomers, (5) 1133

Shear modulus, of elastomers in compression, (5) 1133

Silanes, coupling agents in model compound vulcanization, (1) 27 Silica, effect on model compound vulcani-

zation, (1) 27 interaction with functionalized SBR, (1)

Skid resistance, of shoe soles (review), (3) 512

Soap, free, in SBR latex, (4) 1006 Soles, shoe, factors governing slippage (re-

view), (3) 512 Sour hydrocarbons, fluoroelastomer resistance to, (5) 1269

S. S-di(isopropyl)-N-(p-toluenesulfonyl) sulfilimine, prevulcanization inhibitor, (5) 1106

Standard deviation, test variability estimation by, (2) 384 Starter, automotive, elastomeric, (2) 335

Statistical experimental design, use in testing and problem solving, (2) 385 Steel, abrasion by rubber, (1) 176

solventless BR adhesives for, (2) 285 Strain, effect on elastomer Tp (4) 982

Strain energy density, of elastomers, (4) 836 Stress relaxation, during rubber mixing, (2)

of NR gum vulcanizates, (4) 805 Stress softening, of SBS block polymers, (5) 1124

Stress-strain properties, chain length distribution effects in peroxide-cured elastomers, (4) 988

mathematical description of, (4) 836 of GR versus NR, (2) 385 Structure, carbon black, (2) 382

carbon black, hysteresis effect, (5) 1272 Styrene, butadiene block polymer, bitumen

blends, (4) 994 butadiene block polymer, dynamic properties of, (5) 1124

butadiene block polymer, rheology of, (5)

Styrene-butadiene rubber (SBR), antioxidant efficiency in, (2) 378 ¹³C NMR analysis of, (5) 1191

carbon black dispersion in, (1) 48 cutting resistance of, (1) 210

enthalpic analysis of vulcanization, (1) 160

free soap in latices, (4) 1006

functionalized, silica interaction with, (1)

hydrocarbon resin effect on vulcanization, (2) 386

latex mixture with bitumen, (1) 88 metal wear by, (1) 176

optimization of carbon black loading, (5) 1272

oxygen effect on compression set, (5) 1273 use of recycled rubber in, (5) 1215

Sulfilimines, N-sulfonyl, as prevulcanization inhibitors, (5) 1106

Sulfur, donor effect on model compound vulcanization, (1) 27

Surface area, of carbon black, (2) 382

Suspension bushings, automotive, service life of, (2) 368 Swelling, of peroxide-cured NR, (1) 116

Systematic analysis, of rubber compounds, (2) 387

Temperature, tire, monitoring via thermographic scanner, (2) 381

Tetrahydrofuran, urethane elastomers foam polyether glycols of, (5) 1032

Textiles, energy requirements for manufac-

ture, (5) 1265 Thermal analysis, elastomer characterization by, (5) 1267

of aminimide tire cord adhesives, (2) 270 Thermal conductivity, biaxial orientation effect on, (1) 80

Thermal degradation, of IR, dynamic modulus changes during, (4) 944 Thermal expansion, of NR, (2) 313

Thermographic scanner, tire temperature

monitoring, (2) 381 Thermogravimetry, of elastomers (review),

Thermomechanical analysis (TMA), elastomer characterization by (review), (3) 437; (5) 1267

Thermoplastic elastomers, as cord insulation, (2) 382

EPDM-polypropylene blends, (1) 141 for bitumen modification, (4) 994 nylon-NBR blends, (4) 781 structure of (review), (3) 728

The movision 680, tire temperature profiles, (2) 381

Thiazolesulfenamides, rubber accelerators (review), (3) 393

Thin layer chromatography, rubber compound reconstruction, (2) 383

Thiocarbamylsulfenamides, rubber accelerators (review), (3) 393

Thiomides, prevulcanization inhibitors (review), (3) 393

Thiosulfonamides, prevulcanization inhibitors (review), (3) 393

Thiourea, model compound vulcanization

effect, (1) 27

Tires, calculation of state of cure, (5) 1023 high speed performance-rolling resistance relations, (5) 1271

rolling resistance reduction in, (2) 386 Tire compounds, systematic analysis of, (2) 387

Tire cord, aminimide adhesives for, (2) 270 deformation analysis of, (4) 849 dry bonding adhesives for, (4) 795 modulus effect on rolling deformation, (5) 1271

rolling resistance effect, (3) 600 rubber adhesive, test for, (4) 950

Tire load inflation, calculation of, (2) 229 Tire mechanics, stress characterization, (4) 849

Tire testing, temperature profile scanning during, (2) 381 Tire tread, carbon black hysteretic effects,

(5) 1272

optimum carbon black loading in, (5) 1272 use of recycled rubber in, (5) 1215

Tire wear, environmental effects of, (4) 903 Titanates, polyphosphazene elastomer coupling agents, (2) 391

Titanium dioxide, rheological effects on polystyrene melts, (4) 823

Triazine sulfenamide, rubber accelerator (review), (3) 393

Urethane elastomers, raw materials for, (1)

UV spectra, of rubber, in compound reconstruction, (2) 383

Valanis-Landel hypothesis, elastomer stress-strain behavior, (4) 836

Vibration isolation, rubber usage for, (5)

Viscoelasticity, non-linear, of NR, (4) 805 of elastomers, by thermal analysis, (5) 1267 of NBR, (1) 14

small strain, (5) 1145

Viscometry, solution, NR long chain branching determination, (2) 377

Viscosity, of fiber and filler-loaded polystyrene, (4) 823

of rubber-bitumen mixtures, (1) 88 rubber, effect on mixing efficiency, (2)

zero shear, of viscous liquids, (4) 842 Vulcanization, analysis of by DTA and DSC (review), (3) 437

- continuous, energy requirements for, (5)
- model compound, filler effect, (1) 27 of tires, state of cure calculation for, (5)
- 1023
- Water resistance, of brominated BR adhesives, (2) 285
- Wear, of metals by rubber, (1) 176 Window channel, systematic analysis of, (2) 387
- Zinc, fatty acid salts as processing aids, (2)
- Zinc peroxide, carboxylated NBR/PVC blend curative, (5) 1262